Fiche de produit

Fabricant		DAIKIN
Outdoor unit		3MXF68A2V1B9
Indoor unit		CTXF20F5V1B
Indoor unit		CTXF20F5V1B
Indoor unit		CTXF25F5V1B

Niveau de puissance sonore extérieur (dB)	dB(A)	61.0
Niveau sonore intérieur	dB(A)	54.0
Le réfrigérant (PRG)		R-32 (675)

Mode rafraîchissement

SEER		6.6528664072632955
Classe d'efficacité énergétique		A++
Annual electricity consumption	kWh/a	342.0
Charge de calcul Pdesignc	kW	6.5

Mode chauffage : Climat tempéré
Température de calcul = -10°C

SCOP		4.020170731707318
Classe d'efficacité énergétique		A+
Annual electricity consumption	kWh/a	1845.0
Charge de calcul Pdesignh à -10°C	kW	5.3
Puissance de chauffage de secours nécessaire à -10°C	kW	1.37
Puissance requise de l'appoint de chauffage à -10°C	kW	3.93

Mode chauffage : Climat chaud
Température de calcul = 2°C

SCOP		
Classe d'efficacité énergétique		
Annual electricity consumption	kWh/a	
Charge de calcul Pdesignh à 2°C	kW	
Puissance requise de l'appoint de chauffage à 2°C	kW	
Puissance déclarée à 2°C	kW	

Mode chauffage : Climat froid
Température de calcul = -22°C

SCOP		
Classe d'efficacité énergétique		
Annual electricity consumption	kWh/a	
Charge de calcul Pdesignh à -22°C	kW	
Puissance requise de l'appoint de chauffage à -22°C	kW	
Puissance déclarée à -22°C	kW	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Consommation d'énergie basée sur les résultats de test standard. La consommat on d'énergie réelle dépendra de la manière dont l'appareil est utilisé et de son emplacement.